



# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY FOR CANADA


PRODUCT NAME	VAPOR LOCK™ 20/23		
PRODUCT USE	Water-based concrete admixture that stops the route of moisture migration		
MANUFACTURER'S NAME	SPECIALTY PRODUCTS GROUP 6254 SKYWAY RD., PO BOX 915 SMITHVILLE, ON. L0R 2A0	TEL 1-877-957-4626 FAX 905-527-0606	SPECIALTY PRODUCTS GROUP 3909 Witmer RD, Suite 1014 NIAGARA FALLS, NY 14305
EMERGENCY NUMBER	613-996-6666 OR *666 CANUTEC 1-800-535-5053 UNITED STATES POISON INFORMATION CENTRE		

## 2. HAZARDS IDENTIFICATION



GHS07

ROUTE OF ENTRY	Eye contact, Ingestion, Inhalation, Skin contact.
CARCINOGENIC STATUS	Not considered carcinogenic by NTP, IARC, and OSHA.
TARGET ORGANS	Eye, Skin, and lungs
HEALTH EFFECTS – EYE	Moderate irritation expected
HEALTH EFFECTS – SKIN	Moderate irritation expected.
HEALTH EFFECTS – INGESTION	May cause irritation to the mouth, esophagus and stomach and damage to kidney, central nervous system and blood.
HEALTH EFFECTS – INHALATION	Spray mist is irritating to the respiratory system.



NFPA

HEALTH	4
FLAMMABILITY	5
REACTIVITY	5
PERSONAL PROTECTION	5

HMIS

5-MINIMAL; 4-SLIGHT; 3-MODERATE; 2-HIGH; 1-EXTREME

## 3.COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS NUMBER	WEIGHT %	TWA Ppm	LD50 ORAL RAT Mg/kg	LC50 INHAL RAT ppm
SILICIC ACID, SODIUM SALT PROPRIETARY BLEND	1344-09-8	5-25	NA	NA	NA

## 4. FIRST AID MEASURES

FIRST AID – INHALATION	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention.
FIRST AID – SKIN	Immediately flood the skin with large quantities of water. Remove contaminated clothing and shoes. Obtain medical attention.
FIRST AID – EYE	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention.
FIRST AID – INGESTION	If swallowed, Obtain medical attention immediately. If victim is fully conscious, give a cupful of milk. If conscious induce vomiting. Never give anything by mouth to an unconscious person.

### INFORMATION FOR DOCTOR

**Most important symptoms and effects, both acute and delayed.**

No further relevant information

**Indications of any immediate medical attention and special treatment needed.**

No further relevant information available.

## 5. FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY	Non-flammable. Will not support combustion.
EXTINGUISHING MEDIA	Is compatible with all extinguishing media.
SPECIAL HAZARDS OF PRODUCT	Dries to form glass film which can easily cut the skin. Spilled material is very slippery. Can etch glass if not promptly removed.
PROTECTIVE EQUIPMENT FOR FIRE FIGHTING	Wear full protective clothing when this material is present in the area of the fire.
EXPLOSION DATA – SENSITIVITY TO IMPACT	N/A
EXPLOSION DATA – SENSITIVITY TO STATIC DISCHARGE	N/A

## 6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES	Small spills – Mop up and neutralize liquid, dispose in accordance with federal, provincial and local regulations or permits. Large spills – Isolate hazard area. Do not touch or walk through spilled material. Isolate, dike and store discharged material, if possible. Use sand or earth to contain material. If containment is impossible, neutralize contaminated area and flush with large quantities of water.
PERSONAL PRECAUTIONS	Wear chemical goggles, body-covering protective clothing, chemical resistant gloves and rubber boots. Use a NIOSH-approved dust and mist respirator where spray mist occurs.
ENVIRONMENTAL PRECAUTIONS	Prevent the material from entering drains or watercourses. Notify authorities if spill has entered watercourse or sewer.
<b>REFERENCES TO OTHER SECTIONS</b>	
See Section 7 for information on safe handling See Section 8 for information on personal protection equipment See Section 13 for disposal information	

## 7. HANDLING AND STORAGE

HANDLING	Avoid contact with eyes, skin and clothing. Avoid breathing mist. Keep container closed. Promptly clean up spills.
STORAGE	Keep container closed. Store in clean steel or plastic containers. Separate from acids, reactive metals and ammonium salts. Storage temperature 0-95 deg C. Do not store in aluminum, fiberglass, copper, brass, zinc or galvanized containers.
<b>INFORMATION ABOUT PROTECTION AGAINST EXPLOSION AND FIRE</b>	
Keep ignition sources away – Do not smoke Protect against electrostatic charges	
<b>SPECIFIC END USE(S)</b>	
No further relevant information available	

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.
RESPIRATORY PROTECTION	Use a NIOSH-approved dust and mist respirator where spray mist occurs. Observe Provincial regulations for respiratory use.
EYE PROTECTION	Chemical goggles should be worn during all handling operations to protect against splashing.
BODY PROTECTION	Discard contaminated protective equipment. If there is danger of splashing, wear overall or apron.
PROTECTION DURING APPLICATION	During application, adequate ventilation must be provided. Mix in a well-ventilated area. If ventilation is poor, wear respiratory protection. Dries to form glass film which can easily cut the skin. Spilled material is very slippery. Can etch glass if not promptly removed.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
ODOUR & APPEARANCE	Odorless, clear
ODOR THRESHOLD (ppm)	NA
SPECIFIC GRAVITY	1.07 – 1.10
VAPOR DENSITY (AIR = 1)	ND
VAPOR PRESSURE 20 C	ND
EVAPORATION RATE	ND
BOILING POINT (°C)	ND
FREEZING POINT (°C)	ND

pH	ND
COEFFICIENT OF WATER/OIL DISTRIBUTION	ND
SOLUBILITY IN WATER	Miscible
VOC (g/l)	0
FLASH POINT (PMCC) (°C/F)	Non-flammable.
UPPER FLAMMABLE LIMIT %VOL	NA
LOWER FLAMMABLE LIMIT %VOL	NA
AUTOIGNITION TEMP (°C/F)	NA

## 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal conditions
CONDITIONS TO AVOID	Do Not Freeze
MATERIALS TO AVOID	Gels and can generate heat when mixed with acid. May react with ammonium salts resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead and zinc. May react with strong oxidizing agents.
HAZARDOUS POLYMERIZATION	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS	Hydrogen gas.

## 11. TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE	Irritation to the eyes and skin is expected. Irritation and burning sensation of mouth, throat, nausea, vomiting and abdominal pain. On inhalation of liquid will cause irritation to mucous membranes, coughing and wheezing.
EFFECTS OF CHRONIC EXPOSURE	May cause dermatitis and irritation on repeated contact.
EXPOSURE LIMITS	NA
IRRITANCY	Moderate irritation expected
SENSITIZATION	ND
CARCINOGENICITY	Not listed as a carcinogen by IARC, NTP or OSHA.
REPRODUCTIVE TOXICITY	ND
TERATOGENICITY	ND
MUTAGENICITY	ND
TOXICOLOGICALLY SYNERGISTIC PRODUCTS	ND

## 12. ECOLOGICAL INFORMATION

MOBILITY	Sinks and mixes with water. Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica.
PERSISTENCE/DEGRADABILITY	This product is not persistent in aquatic systems, but its high pH when undiluted or unneutralized is harmful to aquatic life. Full ecological impact has not been determined.
BIO-ACCUMULATION	Neither silica nor sodium will appreciably bioconcentrate up the food chain.
ECOTOXICITY	The following data is reported for sodium silicate on a 100% basis: A 96 hour median tolerance for: Fish ( <i>Gambusia affinis</i> ) of 2320 ppm; Water fleas ( <i>Daphnia magna</i> ) of 247 ppm; Snail eggs ( <i>Lymnea</i> ) of 632 ppm; (Amphipoda) of 160 ppm.

### RESULTS of PBT and vPvB Assessment

PBT: N/A  
vPvB: N/A

## 13. DISPOSAL CONSIDERATIONS

PRODUCT DISPOSAL	Absorb product on an inert material (sand or earth) and transfer absorbed product into a waste container. Dispose of in accordance with all applicable local and national regulations.
CONTAINER DISPOSAL	Labels should not be removed from containers until they have been cleaned. Empty containers may contain hazardous residues. Dispose of containers with care.

### UNCLEANED PACKAGINGS

Recommendation: Disposal must be made according to official regulations

## 14. TRANSPORTATION INFORMATION

CANADA	TDG CLASSIFICATION
--------	--------------------

HAZARD LABEL	NOT REQUIRED	NOT REGULATED, Keep from freezing
<b>EXPORT</b>		
DOT CFR 172.101 DATA		NOT REGULATED
UN PROPER SHIPPING NAME		NA
UN CLASS		NA
UN NUMBER		NA
UN PACKAGING GROUP		NA
FLASH POINT		NA
HAZARDOUS MATERIAL		NA
HAZARD LABEL		NA
MARINE POLLUTANT		NO
SPECIFIC PRECAUTIONS FOR USER		M/A

## 15. REGULATORY INFORMATION



WHMIS CLASSIFICATION: CLASS D, DIV.2, SUBDIVISION B-Material causing other toxic effects.

CEPA STATUS (DSL) : All of the ingredients of this product are listed on the Domestic Substances List.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by CPR.

## 16. OTHER INFORMATION

HAZARD RATING (HMIS)	HEALTH: 4	FLAMMABILITY: 5	REACTIVITY: 5
KEY	5-MINIMAL; 4-SLIGHT; 3-MODERATE; 2-HIGH; 1-EXTREME		
PREPARED BY:	Specialty Products Group Inc.		

NA: No applicable information found or available  
CAS#: Chemical Abstracts Service Number  
ACGIH: American Conference of Governmental Industrial Hygienists  
OSHA: Occupational Safety and Health Administration  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
STEL: Short Term Exposure Limit  
NTP: National Toxicology Program  
IARC: International Agency for Research on Cancer  
R: Risk  
S: Safety  
LD50: Lethal Dose 50%  
LC50: Lethal Concentration 50%

SDS REVISION DATE

October 4, 2018

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.